



SRK 600 RR (QJ600GS-3B)



RACING REPLICA

QJ600GS-3B



1. 600 cc inline 4-Cylinder, DOHC, 16 valves, Liquid-cooled engine (with improved lightweight connecting rod, piston, and balance shaft)
2. Assist and slipper clutch & mono-directional quick shifter + Clip-on Handlebar + backlit switch assembly
3. High tensile steel trellis frame with Magnesium Aluminum Alloy swingarm.
4. KYB Suspension Front upside-down fork / Rear adjustable mono shock
5. Brembo calipers Front (double disc, radial master cylinder) and Rear + Bosch dual channel ABS

DIMENSIONS

Overall L*W*H(mm)	2,140X750X1,150
Wheel Base (mm)	1,460
Seat Height (mm)	800
Ground Clearance (mm)	140
Curb Weight (kg)	215
Max.Capacity (persons)	2

FRAME

Type	Trellis/Steel&Alloy
Front Suspension/Travel (mm)	Telescopic
Rear Suspension/Travel (mm)	Unit Swing
Front Tyre/Type	120/70-17 Tubeless
Rear Tyre/Type	180/55-17 Tubeless
Front Brake (mm)	Hydraulic Disk Ø320(Double)
Rear Brake (mm)	Hydraulic Disk Ø260
Fuel Capacity (L)	16.4

ENGINE

Type	4-Stroke Liquid-Cooled
Cylinder Arrangement	Inline 4-Cylinder
Bore × Stroke (mm)	65.0 x45.2mm
Displacement (cm ³)	600
Compression Ratio	11.5:1
Valve Train	DOHC 16V
Maximum Horsepower (kW/rpm)	60.0/11,000
Maximum Torque (Nm/rpm)	55.0/8,000
Fuel System	EFI
Lubrication System	Forced and Splash

DRIVE

Clutch	Manual,Multiplate Wet Clutch(with ASC)
Transmission	Chain
Gear Shift Pattern	1-N-2-3-4-5-6(Quickshifter)

ELECTRICAL

Ignition System	TCI
Starting System	Electric

+86576 86139262 @QJMOTOR www.qjmotor.com

