FAW

Unique & Reliable For All Loads

J5M-220

Super Plus (4x2) Prime Mover

Euro-II

2 Years or WARRANTY 120,000km whichever comes first

Powerful, Reliable, Fuel Efficient Engine | Robust Cabin with AC | Heavy Duty Gear Box | 11 Radial Tyres

J5M-220 Super Plus (4x2) Prime Mover

SPECIFICATIONS

MASS		ماس
Permisible G.C.W (Kg)	35000	پرمیسیبل
Axle Load Distribution (kg)		ایکسل لوڈ کی تقسیم
Front	6000	فرنٹ
Rear	12000	ریئر
Chasis Weight (Kg)		چیسس ویٹ
Total	5360	ٹوٹل
Front	3290	فرنٹ
Rear	2070	ریئر
PERFORMANCE		کارکردگی
Max. Speed (km/h)	90	رفتار (کلومیٹر فی گھنٹہ)
Max. Gradeability (%)	29	گریڈ ایبلیٹی
Fuel Tank Capacity (L)	400	گنجائش (لیٹر)
ENGINE		انجن
Model	FAWDE CA6DF2D-22	ماڈل
Type	Diesel, 4-stroke in-line, 6 cylinders, water cooled, turbo charged with inter cooler	ٹائپ
Max. Output Power (hp/rpm)	220 @ 2300	حد کارکردگی
Max. Torque (Nm/rmp)	770 @ 1400	حد ٹارک
Displacement (cc)	6557 (6.5 Litter)	ڈسپلیسمنٹ (سی سی)
Bore	110x115	بور
Emission Standard	Euro II	امیشن اسٹینڈرڈ
TRANSMISSION		ٹرانسمیشن
Model	FAW CA7TBLOOOM	ماڈل
Type	7 Forward 1 Reverse (Inclusive of "C" Gear)	ٹائپ
Gear Ratio	i1 = 10.120/ i2 = 7.270/ i3 = 4.310/ i4 = 2.718/ i5 = 1.826/ i6 = 1.342/ i7 = 1.000	گیئر ریشیو
Reverse Shift Ratio	Ir = 9.397	ریورس شفٹ تناسب
CLUTCH		کلچ
Type	Eaton dry type, single plate, diaphragm spring clutch, hydraulic controlled and air aided power Operating	ٹائپ
Driven Plate Dia.	395 (15.5)	ڈرائیون پلیٹ ڈایا
AXLES		ایکسلز
Front	Reverse elliot "I" section beam	فرنٹ
Rear	FAW Single Reduction	ریئر
Ratio	6.33	ریشیو
BRAKES		بریک
Driving Brake	Full air dual circuit brake	ڈرائیون بریک
Parking Brake	Spring energy storage type	پارکنگ بریک
Auxiliary Brake	Exhaust brake	اگزاسٹ بریک
STEERING		اسٹیرنگ
Type	Recirculating ball-type steering, integrated power steering	ٹائپ
SUSPENSION		سسپنشن
Front	Semi-elliptic multi-leaf springs	فرنٹ
Rear	Semi-elliptic multi-leaf main springs with auxiliary springs	ریئر
WHEEL		وہیل
Rim	8.00-20	رِم
Wheel Type	Stud-piloted 8-hole steel disk	وہیل ٹائپ
Tyre size	11.00-20R	ٹائر سائز
No. of Tyres	7	نمبر آف ٹائرز
Turning Radius (m)	8.5	ٹرننگ ریڈیئس
FRAME		فریم
Type	Side rails, punching & riveted construction	ٹائپ
Main Rail section	280x80x8	مین ریل سیکشن
CAB		کیب
Type	Cab over engine, front tilting 44 Angle	ٹائپ
Suspension	2-point hydraulic sespension	سسپنشن
Seats Type	Mechanical suspension seat with 3-point seat belt	سیٹس ٹائپ
Seating Capacity	2	سیٹوں کی گنجائش
ELECTRICAL SYSTEM		الیکٹریکل سسٹم
Type	Single line, Negative earthed	ٹائپ
Generator	1200 W	جنریٹر
Battery (V/Ah)	2 x 12V / 120	بیٹری

Note: AHFM reserves the right to change the specifications and desgin for the immprovement of the product at any time

Regional Sales Office

Karachi
D-55/A, SITE Main Estate,
Avenue Road, Karachi.
Tel: 021-32573251-3
Fax: 021-32153252

Lahore (Central)
Off # 104 & 105 First Floor,
EDEN Height, 6 Gulberg,
Jail Road, Lahore.
Tel: 042-35786805

Peshawar
Landi Akhun Ahmed,
Near Sarhad University,
Ring Road Peshawar
Tel:091-5230003-4

Islamabad
2nd Floor, Office # 02
Rafay Mall,Near Chowk,
Peshawar Road Rawalpindi
Tel: 051-5166937-0

3S Dealerships (Sale, Service & Parts)

FAW Ravi Motors
FAW RAVI Motors
13-km, Multan Road,
Mohlanwal Chowk,
Lahore.

FAW Sadiqabad Motors
KLP Road, Bashir Sidique,
Market Machi Goth,
Sadiqabad, Punjab.
Tel: 0307-2240221

FAW Abdali Motors
Bypass Muzaffar,
Garh Road, Multan.
Tel: 0307-2240221

FAW Faisalabad Motors
2 km, Sidhar Bypass,
Chowk Jhang Road,
Faisalabad, Punjab.
Cell: 0300-0250400

FAW Federal Motors
Near Zila Tax, Main GT
Road, Tarnol, Islamabad.
Cell: 0320-5519947

FAW Peshawar
Landi Akhun Ahmed,
Ring Road Peshawar.
Tel: 091-5230003-4

Head Office / Assembly Plant: Main National Highway, Zulfiqarabad Karachi,
Tel: (92-21)34100335-8 Fax: (92-21)34100922, UAN No, (92-21) 111-092-111 Website: www.alhajfaw.com