



# FAW

Unique & Reliable For All Loads

# J5M-220

Super Plus (6x2) Rigid Truck



 Euro-II



Powerful, Reliable, Fuel Efficient Engine | Robust Cabin with AC | Heavy Duty Gear Box | 11 Radial Tyres

# J5M - 220 Super Plus (6x2) Rigid Truck

## SPECIFICATIONS

MASS		TRANSMISSION		DIMENSIONS	
Permissible G.C.W (Kg)	28,500	Model	FAW CA7TB100M	Length (mm)	9845
Axle Load Distribution (kg)	ایکسل لوڈ کی تقسیم	Type	7 forward 1 reverse (inclusive of 'C' gear)	Width (mm)	2490
Front	6,500	Gear Ratio	i1=10.120/ i2=7.270/ i3=4.310/ i4=2.718/ i5=1.826/ i6=1.342/ i7=1.000	Height (mm)	2720
Rear	22,000	Reverse Shift Ratio	Ir = 9.397	Length Behind Cab (mm)	7718
Chassis Weight (kg)	چیسس کا کل وزن	<b>CLUTCH</b>	کلیچ	Wheel Base (mm)	4725 +1350
Total	7,800	Type	Eaton dry type, single plate, diaphragm spring clutch, hydraulic controlled and air aided power Operating	Min. Ground Clearance	298
Front	3,800	Driven Plate Dia.	φ395 (15.5)	Front overhang (mm)	1375
Rear	4,000	<b>AXLES</b>	ایکسل	Rear overhang (mm)	2935
<b>PERFORMANCE</b>	کارکردگی	Front	Reverse Elliot "I" section beam	<b>SUSPENSION</b>	سپینشن
Max. Speed (km/h)	85	Rear	FAW single reduction	Front	Semi-elliptic multi-leaf springs
Max. Gradeability (%)	32	Ratio	5.28 (7/37)	Rear	Semi-elliptic, multi-Leaf Main Springs with auxiliary springs
Fuel Tank Capacity (L)	400	<b>BRAKES</b>	بریک	<b>WHEEL</b>	ویل
<b>ENGINE</b>	انجن	Driving Brake	Full air dual circuit brake	Rim	8.00-20
Model	FAWDE CA6DF2D-22	Parking Brake	Spring energy storage type	Wheel Type	Stud-piloted 10-hole steel disc
Type	Diesel, 4-stroke in-line, 6 cylinders, water cooled, turbo charged with inter cooler	Auxiliary Brake	Exhaust brake	Tyre Size	11.00-20R
Max. Output (hp/rpm)	220 @ 2300	<b>STEERING</b>	اسٹیرنگ	No. of Tyres	11
Max. Torque (Nm/rpm)	770 @ 1400	Model/Type	Recirculating ball-type steering, integrated power steering	Turning Radius (m)	8.5
Displacement (cc)	6557 (6.5 litre)	<b>CAB</b>	کیب	<b>FRAME</b>	فریم
Bore	110x115	Type	Cab over engine, front tilting 44 Angle	Type	Side Rails, punching & riveted construction
Emission Standard	Euro II	Suspension	2-point hydraulic suspension	Main Rail section	280x90x8
		Seats Type	Mechanical suspension Seat with 3-Point Seat Belt	<b>ELECTRICAL &amp; LIGHTS</b>	الیکٹریکل اور لائٹس
		Seating Capacity	2	Type	Earth return system, negative earthed
				Battery (V/Ah)	2 x 12V / 150
				Generator	1200 W

### Regional Sales Office

**Karachi**  
D-55/A, SITE Main Estate,  
Avenue Road, Karachi.  
Tel: 021-32573251-3  
Fax: 021-32153252

**Peshawar**  
Landi Akhun Ahmed,  
Near Sarhad University,  
Ring Road Peshawar  
Tel: 091-5230003-4

**Lahore (Central)**  
Off # 104 & 105 First Floor,  
EDEN Height, 6 Gulberg,  
Jail Road, Lahore.  
Tel: 042-35786805

**Islamabad**  
2nd Floor, Office # 02  
Rafay Mall, Near Chowk,  
Peshawar Road Rawalpindi  
Tel: 051-5166937-0

### 3S Dealerships (Sale, Service & Parts)

**FAW Ravi Motors**  
FAW RAVI Motors  
13-km, Multan Road,  
Mohlanwal Chowk,  
Lahore.

**FAW Faisalabad Motors**  
2 km, Sidhar Bypass,  
Chowk Jhang Road,  
Faisalabad, Punjab.  
Cell: 0300-0250400

**FAW Sadiqabad Motors**  
KLP Road, Bashir Sidique,  
Market Machi Goth,  
Sadiqabad, Punjab.  
Tel: 0307-2240221

**FAW Federal Motors**  
Near Zila Tax, Main GT  
Road, Tarnol, Islamabad.  
Cell: 0320-5519947

**FAW Abdali Motors**  
Bypass Muzaffar,  
Garh Road, Multan.  
Tel: 0307-2240221

**FAW Peshawar**  
Landi Akhun Ahmed,  
Ring Road Peshawar.  
Tel: 091-5230003-4

Head Office / Assembly Plant: Main National Highway, Zulfiqarabad Karachi,

Tel: (92-21)34100335-8 Fax: (92-21)34100922, UAN No, (92-21) 111-092-111 Website: www.alhajfaw.com

