




Ghandhara DF (Pvt) Ltd.

Head Office:

F-3, Hub Chowki Road, S.I.T.E, Karachi. UAN # 021-111-190-190, Tel: 021-32556901-10, Fax: 021-32556911-12 Rawalpindi Office:

Gammon House Plot no. 400/2 Peshawar Road, Rawalpindi.

Ph: 051-5465742 **Fax**: 051-5465503



f Dongfeng Pakistan

Lahore Office:

First Floor, Luban's Arcade, Abpara Housing Scheme, Near DHA EME Sector, Main Canal Road, Lahore 042-35451051




■ DONGFENG DFH4180B-KN1Y-981, DF-245, 4x2 Prime Mover

Vehicle Weights		•
G.C.M	39,500 kg	
Curb Weight (chassis)	5,900 kg	

Chassis Dimension	ıs (mm)	_
Overall Chassis Length	6030	
Cab Width	2500	
Cab Height (Unladen)	2880	
Wheel Base	3500	
Front Overhang	1430	
Rear Overhang	1100	
Maximium Speed	95 km/hr	
Gradeability	30%	

Frame Dimension	ns (mm)	•
Frame width (Front)	860	
Frame width (Rear)	860	
Frame Section Height	280	
Frame Section Width	80	

Clutch	•
Туре	Dry Single Plate
Diameter	430mm (17 Inches)
Operating System	Hydraulic control with air booster, pushing.





2880mm

2,500mm

Engine	▼
Make	Cummins
Model	ISDe245 30
Emission Level	EURO III
Maximum Power	245hp at 2500 rpm
Maximum Torque	950 Nm at 1500 rpm
Displacement (lit)	6,700 CC
Number of Cylinders	6
System	Water cooled, turbocharged,
	after cooled, cold start.
Cylinder bore (mm)	107
Stroke (mm)	124



Type 8JS125T DD Number of Gears 8 forward gears & 2 reverse



Axles	▼
Make:	DANA
Front:	Elliot type, I beam section
Load Capacity	7 tons
Rear	Single reduction
Load capacity(ton)	13 tons
Final Ratio:	5.143

Suspension	▼
Front:	8- Leaf spring
Rear:	10+8-leaf spring

Full air brake system, split pneumatic circuit; parking spring brake acting on rear axles, exhaust brake.

Fuel Tank	▼
Туре	Steel fuel tank with lockable cap
Capacity	450 Liters

Cabin

Kingrun one and a half row cab ,forward control type , all welded steel cab of tilt type, mechanical cab tilting, front and rear mechanical cab suspension adjustable driver's seat, air conditioning system, electrical windows,central lock.

Voltage (V): 24
Battery Capacity (A.h) 165X2

Note: The above mentioned parameters are only for your reference, please check real vehicle referring to actual equipment.

